

Induktive Näherungsschalter, 3-Draht

Inductive proximity switches, 3-wire
 Finecorse di prossimità induttivi, 3-fili

P + F NBB2-V3-E2

EB2I
EBA2I
EBP2I
EBS2I

Varianten (Versions / Tipi)




Technische Daten (Technical features / Dati tecnici)

Endschalterfabrikat	P + F
Producer switch / Marca finecorsa	
Endschaltertyp	NBB2-V3-E2 (3-wire, PNP)
Switch type / Tipo finecorsa	
Spannung	10-30V DC
Voltage / Tensione	
Stromaufnahme	100mA
Current / Corrente	
Schaltfrequenz	1000Hz
Frequency / Frequenza	
Leerlaufstrom	15mA
No-load supply current / Corrente minima	
Anzeige	LED gelb (yellow / giallo)
Output indicator / Indicazione	
Schutzart Schalter	IP67 - DIN 40050
Enclosure switch / Protezione finecorsa	
Temperatur	-25°C ... +80°C
Temperature / Temperatura	


Anschlussbild EB/EBA/EBP

Connection / Connessione



Anschlussbild EBS

Connection / Connessione



Adaption (Adoption / Adattamento)

EB	Wellenhöhe Antrieb
Bohrbild Antrieb	Shaft height act. / Altezza perno att.
80 x 30mm	20mm
80 x 30mm	30mm
130 x 30mm	20mm
130 x 30mm	30mm

EBA/EBP/EBS	Wellenhöhe Antrieb
Bohrbild Antrieb	Shaft height act. / Altezza perno att.
80 x 30mm	20mm
80 x 30mm	30mm
80 x 30mm	40mm
80 x 30mm	50mm
130 x 30mm	20mm
130 x 30mm	30mm
130 x 30mm	40mm
130 x 30mm	50mm

Artikelnummer (Code number / Numero codice)

Preisliste Seite 3 Price list page 3 / Listino dei prezzi pagina 3

